

Model 915 Time & Attendance Terminals

Choice of Proximity Barcode, Magnetic Stripe, or Fingerprint Reader
in an Improved, Intuitive, Compact Design



Prox915-125 / Prox915-HID
Proximity card reader



BC-915
Barcode card reader



MG-915
Magnetic card reader



Bio915
Fingerprint reader

Standard Functions

- Wi-Fi Standard Feature on all Devices
- User-Friendly UI and Menu Design
- Hardware-Level Clock Data Input Authentication
- User Level Duplicate Punch Prevention
- Multiple Level Job Code Entry Support
- Enhanced Network Security
- Automatic Status Key Switch
- Supports up to 9 Digit User ID
- Daylight Savings Time Support
- Customizable Bell Schedules
- USB-Host Port Provided
- Private or public SMS messaging support

Terminal Specifications

Capacity

ID Cards: up to 10,000
Transactions: up to 100,000
Fingerprint templates: 3,000

Fingerprint Sensor

Optical

Display

3.0 in. TFT Color Screen

Communications

Ethernet, USB-Host, Wi-Fi

Power

12 V DC, 1.5 A
Optional: 12V POE injector (sold separately)
Optional: 12V Battery Backup (sold separately)

Environment

Operating Temperature: 32° F to 113° F (0° C to 45° C)
Operating Humidity: 5% to 80%

Supported Devices

Bio915-125 Fingerprint and RFID prox reader
Bio915-HID Fingerprint and HID prox reader
MG-915 Magnetic card reader
BC-915 Barcode card reader
Prox915-125 Standard RFID prox reader
Prox915-HID Standard HID prox reader

Dimensions

Width: 6.5 in. (16.5 cm)
Height: 5.5 in. (14 cm)
Depth: 1.8 in. (4.6 cm)
Weight: 0.95 lbs. (0.43 kg)